

Products Specification

SHENZHEN ABT ELECTRONICS CO., LTD.

E-mail:sales@abt-power.com Web:www.abt-power.com

SPECIFICATION		PREPARE	CHECK	APPROVE
MODEL:	USED IN:			
ISSUE DATE :	2010-08-01			
COMMON/UNITE	DOC. NO:		REV.: 1.0	PAGE: 1 OF 1

3P10-N0512 SMART NIMH BATTERY CHARGER

NO	ITEM	UNIT	SPECIFICATION	REMARK
INPUT				
01	RATING INPUT	V ac	100~240Vac 50/60Hz	
02	INPUT RANGE	V ac	90~264Vac	
03	RATING INPUT CURRENT	A	0.1Arms	INPUT:220V OUTPUT:Full load
04	MAX. INPUT POWER	W	6	
OUTPUT				
05	RATING OUTPUT VOLTAGE	V dc	9.6Vdc	
06	OUTPUT VOLTAGE RANGE	V dc	6 ~ 13Vdc	
07	SUIT WITH BATTERY	Ah	6.0~7.2V 0.4~3.2Ah NIMN/NICD	
08	CHARGE CURRENT	A	0.3A ~0.5A	
09	TRICKLE CURRENT	A	<0.05	
11	INNER TIMMER	hour	8	T.B.D. 1~10 hours
12	MAX. OUTPUT POWER	W	4W	
13	HOLD-ON TIME	ms	NC	Input: 220Vac Output: Full load
14	RIPPLE CURRENT	mA	30	Input: 220Vac Output: Full load
15	MAIN CHARGE END CONDITION		- $\Delta V > 5mV$ /CELL(TYP) or $V_{MAX} \geq 9.6V$ or Timer out.	
16	LED INDICATION		RED: MAIN CHARGE GREEN: FINISHED	
17	SHORT CIRCUIT PROTECT	-	YES	OUT CURRENT < 0.2A
18	EFFICIENCY	%	70%	At max. load
ENVIRONMENT				
19	OPERATE TEMP.	°C	-10 ~ +40	Full load & natural convection.
20	OPERATE HUMIDITY	%RH	< +90	Relative humidity, non-condensing.
21	STORAGE TEMP.	°C	-40 ~ +70	
22	STORAGE HUMIDITY	%RH	0 ~ +95	Relative humidity, non-condensing.
23	COOLING	-	Natural convection	
24	TEMP. FACT	%	--	
25	VIBRATION		5MM/50HZ/600S	Non-operating condition.
26	IMPACT		1 meter drop test ≥ 3 times	Non-operating condition.
MECHANICAL				
27	WEIGHT	g	120	
28	SIZE	mm	75X51X28	Casing only
29	CONNECTER	-	DC PLUG: Bare Barrel (typical 5.5x2.1x10mm) or others type. AC PLUG: Defined when order	
SAFETY				
30	TEMP. RISE	°C	< 40 on casing	At any line and Max. Load
31	SAFETY STANDARD	-	EN60950	
32	EMC	-	EN55022 B	
33	MTBF	hrs	30000	
34	ESD	kV	8.0	
35	HI-POT	V	i/p to o/p: 3000 (1 min.)	For final unit, cut-off current =10mA