

---

---

## P10XX (AXX) 6V~12V Lead-Acid Battery Smart Charger

### Feature:

- Programmed 3 auto stages ( CC-Bulk-Float) charging process.
- Designed for all kinds of 6V~12V 2~12Ah lead-acid battery, such as SLA, AGM and Gel battery.
- With 4 LEDs battery fuel gauge indicator, easily know the charging process and charged capacity.
- Protection mode for battery polarity reversed or the output connectors shorted.
- UL, CE approval (EN60335-2-29 and UL1310)



### Specification for P10XX

Input Voltage	100-240VAC, 50-60Hz	
Input Current	0.2A rms	
Back current drain	1.3mA	
Bulk voltage Limited	<b>P1007 (A6)</b>	<b>P1015 (A12)</b>
	7.3V	14.5V
Bulk charge current	1.2A	0.8A
Floating voltage	6.8V	13.6V
Operate Temperature	-20℃~40℃ ,	
Cooling	Natural convection. Do not cover the charger.	
Charge principle	Auto 3 stages: CC—CV(Bulk)--Floating	
Battery type	All types of 6V~12V lead-acid batteries.( SLA, Gel, AGM....)	
Battery capacity	4--12Ah	
Size	81X43X30mm	
Output cable and plug	1.2 meter 2xAWG22#, UL2468 wire, 5.5x2.1x10mm plug	
Input plug	US or VDE	
Enclosure	IP54 (Dust protected, Water splashing resistance)	
Weight	100g	